



Dimensions are in millimeters and include label.

Chemical system:	Nickel-Metal Hydride, Precharged
Designations:	IEC HR6, ANSI 1.2H2
Nominal Voltage:	1.2V
Nominal Capacity:	2100 mAh
Rated, Minimum Capacity: (IEC/EN 61951-2)	2000 mAh
Charging Condition:	210 mA for 16h
Maximum continuous discharge:	4.0 A to 1.0 V
Maximum intermittent discharge:	6.0 A
Minimum charging cycles:	1000
Average Weight:	28.0 g
Recommended storage temperature:	5 – 20 °C
Operating temperatures:	0 – 50 °C
Terminals:	Flat contacts
Jacket:	PVC Label

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) Batteries are NOT subject to European RoHS regulations.
- 7) MSDS sheets are available on request from Strand Europe Ltd.
- 8) Charge or Discharge at extreme high or low temperature will significantly affect service and cycle life.
- 9) For best performance after long period of non-use, charge and discharge the battery several times.

