



<b>Chemical System:</b>	Lithium/Iron Disulfide, Li/FeS <sub>2</sub>
<b>Designations:</b>	IEC FR6
<b>Nominal Voltage:</b>	1.5V
<b>Nominal Capacity:</b>	2600 mAh at 75 Ohms to 0.8 Volts
<b>Camera Performance:</b>	Up to x9 more photos than Kodak Xtralife batteries
<b>Internal Impedance:</b>	0.25 Ohms (typically)
<b>Average Weight:</b>	14.5 g
<b>Average Volume:</b>	8.0 cm <sup>3</sup>
<b>Recommended Storage Temperature:</b>	-40°C to 60 °C
<b>Operating Temperatures:</b>	-40°C to 60 °C
<b>Reaction:</b>	$2 \text{ Li} + \text{ FeS}_2 \rightarrow \text{ Li}_2\text{FeS}_2$
<b>Terminals:</b>	Flat contacts, protruding negative
<b>Jacket:</b>	Plastic label
<b>Lithium Content:</b>	Under 1 g

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with IEC 60086-4 and EU Directive 2006/66/EC, 2006/122/EC
- 6) Primary Batteries (non-Rechargeable) are not subject to European or Chinese RoHS regulations.
- 7) MSDS are available at [www.kodakbatteries.strandeuropa.com](http://www.kodakbatteries.strandeuropa.com) and on request from Strand Europe Ltd.