



| | |
|---|---|
| Chemical system: | Alkaline, MnO_2 / KOH / Zn |
| Designations: | IEC LR6, ANSI 15A |
| Nominal Voltage: | 1.5V |
| Nominal Capacity: | 2700 mAh at 75 Ohms to 0.8 Volts |
| Internal Impedance: | 0.15 Ohms (typically) |
| Average Weight: | 23.0 g |
| Average Volume: | 8.0 cm ³ |
| Recommended storage temperature: | 10 – 25 °C |
| Operating temperatures: | -20 – 54 °C |
| Reaction: | $2 \text{MnO}_2 + \text{Zn} + \text{H}_2\text{O} \rightarrow 2 \text{MnOOH} + \text{ZnO}$ |
| Terminals: | Flat contacts, protruding negative |
| Jacket: | Plastic label |

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead / 99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) Batteries are NOT subject to European RoHS regulations.
- 7) Primary Batteries (non-Rechargeable) are not subject to China RoHS regulations.
- 8) MSDS sheets are available on request from Strand Europe Ltd.