



Dimensions are in millimeters and include label.

Chemical system:	Nickel-Metal Hydride, Precharged
Designations:	IEC HR6, ANSI 1.2H2
Nominal Voltage:	1.2V
Nominal Capacity:	2100 mAh
Rated, Minimum Capacity: (IEC/EN 61951-2)	2000 mAh
Charging Condition:	210 mA for 16h
Maximum continuous discharge:	4.0 A to 1.0 V
Maximum intermittent discharge:	6.0 A
Minimum charging cycles:	1000
Average Weight:	28.0 g
Recommended storage temperature:	+5 – +25 °C, RH no more than 75%
Operating temperatures:	0 – 50 °C
Terminals:	Flat contacts
Jacket:	PVC Label

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) SDS sheets are available on request from Strand Europe Ltd.
- 7) Charge or Discharge at extreme high or low temperature will significantly affect service and cycle life.
- 8) For best performance after long period of non-use, charge and discharge the battery several times.



Brand Licensee
KODAK Batteries
KODAK LED Bulbs
KODAK Headphones
KODAK LED Flashlights

The Kodak trademark, logo and trade dress are used under license from Kodak.
© 2021 STRAND EUROPE LTD.
www.kodakbatteries.strandeurope.com